

Hexane, 2,2,3,4-tetramethyl-

| | |
|-----------------------------|---|
| Other names: | 2,2,3,4-Tetramethylhexane |
| Inchi: | InChI=1S/C10H22/c1-7-8(2)9(3)10(4,5)6/h8-9H,7H2,1-6H3 |
| InchiKey: | MHPSPNGWFAGBNH-UHFFFAOYSA-N |
| Formula: | C10H22 |
| SMILES: | CCC(C)C(C)C(C)(C)C |
| Mol. weight [g/mol]: | 142.28 |
| CAS: | 52897-08-2 |

Physical Properties

| Property code | Value | Unit | Source |
|---------------|---------------|----------------------|----------------|
| gf | 31.28 | kJ/mol | Joback Method |
| hf | -269.04 | kJ/mol | Joback Method |
| hfus | 7.20 | kJ/mol | Joback Method |
| hvap | 45.60 | kJ/mol | NIST Webbook |
| log10ws | -3.28 | | Crippen Method |
| logp | 3.715 | | Crippen Method |
| mcvol | 151.760 | ml/mol | McGowan Method |
| pc | 2177.49 | kPa | Joback Method |
| rinpol | 908.80 | | NIST Webbook |
| rinpol | 909.00 | | NIST Webbook |
| rinpol | 903.00 | | NIST Webbook |
| rinpol | 909.00 | | NIST Webbook |
| rinpol | 902.80 | | NIST Webbook |
| rinpol | 909.00 | | NIST Webbook |
| rinpol | 915.00 | | NIST Webbook |
| tb | 432.00 ± 1.00 | K | NIST Webbook |
| tb | 427.50 ± 1.50 | K | NIST Webbook |
| tc | 604.51 | K | Joback Method |
| tf | 174.88 | K | Joback Method |
| vc | 0.573 | m ³ /kmol | Joback Method |

Temperature Dependent Properties

| Property code | Value | Unit | Temperature [K] | Source |
|---------------|-------|------|-----------------|--------|
|---------------|-------|------|-----------------|--------|

| | | | | |
|-------|-----------|---------|--------|---------------|
| cpg | 316.88 | J/molxK | 424.09 | Joback Method |
| cpg | 334.37 | J/molxK | 454.16 | Joback Method |
| cpg | 351.04 | J/molxK | 484.23 | Joback Method |
| cpg | 366.91 | J/molxK | 514.30 | Joback Method |
| cpg | 382.02 | J/molxK | 544.37 | Joback Method |
| cpg | 396.39 | J/molxK | 574.44 | Joback Method |
| cpg | 410.05 | J/molxK | 604.51 | Joback Method |
| dvisc | 0.0446565 | Paxs | 174.88 | Joback Method |
| dvisc | 0.0079881 | Paxs | 216.41 | Joback Method |
| dvisc | 0.0024872 | Paxs | 257.95 | Joback Method |
| dvisc | 0.0010703 | Paxs | 299.49 | Joback Method |
| dvisc | 0.0005656 | Paxs | 341.02 | Joback Method |
| dvisc | 0.0003433 | Paxs | 382.55 | Joback Method |
| dvisc | 0.0002298 | Paxs | 424.09 | Joback Method |

Correlations

| Information | Value |
|-----------------------------|-------------------------------|
| Property code | pvap |
| Equation | $\ln(P_{vp}) = A + B/(T + C)$ |
| Coeff. A | 1.40650e+01 |
| Coeff. B | -3.55370e+03 |
| Coeff. C | -5.57720e+01 |
| Temperature range (K), min. | 313.71 |
| Temperature range (K), max. | 461.75 |

Sources

| | |
|---|---|
| Joback Method: | https://en.wikipedia.org/wiki/Joback_method |
| McGowan Method: | http://link.springer.com/article/10.1007/BF02311772 |
| NIST Webbook: | http://webbook.nist.gov/cgi/cbook.cgi?ID=C52897082&Units=SI |
| The Yaws Handbook of Vapor Pressure: | https://www.sciencedirect.com/book/9780128029992/the-yaws-handbook-of-vapor-pressure |
| Crippen Method: | http://pubs.acs.org/doi/abs/10.1021/ci9903071 |
| Crippen Method: | https://www.chemeo.com/doc/models/crippen_log10ws |

Legend

| | |
|------------------|---|
| cpg: | Ideal gas heat capacity |
| dvisc: | Dynamic viscosity |
| gf: | Standard Gibbs free energy of formation |
| hf: | Enthalpy of formation at standard conditions |
| hfus: | Enthalpy of fusion at standard conditions |
| hvap: | Enthalpy of vaporization at standard conditions |
| log10ws: | Log10 of Water solubility in mol/l |
| logp: | Octanol/Water partition coefficient |
| mcvol: | McGowan's characteristic volume |
| pc: | Critical Pressure |
| pvap: | Vapor pressure |
| rinpolar: | Non-polar retention indices |
| tb: | Normal Boiling Point Temperature |
| tc: | Critical Temperature |
| tf: | Normal melting (fusion) point |
| vc: | Critical Volume |

Latest version available from:

<https://www.cheméo.com/cid/33-994-2/Hexane-2-2-3-4-tetramethyl.pdf>

Generated by Cheméo on 2024-04-26 16:20:25.856276622 +0000 UTC m=+16437674.776853934.

Cheméo (<https://www.cheméo.com>) is the biggest free database of chemical and physical data for the process industry.